Lithium Polymer (Li-Po) Battery Data-sheet

Features of Battery

- No Fire / Explosion
- Massive Range of Li-Po Battery Current
- Massive Range of Battery Applications
- Excellent Charge & Discharge Characteristics

Environmental and Safety

Do not put lithium batteries in fire.

Do not reverse the positive and negative poles of the lithium battery charger.

Do not short-circuit the lithium battery (P+, P-).

Avoid excessive shock and vibration of lithium batteries.

Li-Polymer Battery Dimension



Item	Parameter (mm)
T	4
W	58
M	6/8
L	65
L_1	67
BL	67 ± 1
CL	100



Specification

Electrical Data	Part Number	LP445865
	Nominal Voltage	3.7V
	Nominal Capacity	2500 mAh
	Internal Impedance	< 60mΩ
	Charge Voltage	4.2V
	Recommended Charge Current	0.2C
	Allowed Max Charge Current	0.5C
	Output Voltage Range	4.2 - 2.5V
	Recommend Discharge Current	0.2C
	Max Continuous Discharge Current	1C
	Pulse Discharge Current	3C(10mS)
	Discharge Cut-off Voltage	2.5 ± 0.05V
	Cycle Life to 80% Health	500(0.2C, 25℃)
Environmental Data	Charging Temperature Range	0 - 45℃
	Discharging Temperature Range	-20 - 60℃
	Storage Period 1 Week	-20 - 45℃
	Storage Period 1 Month	-10 - 45℃
	Storage Period 6 Months	0 - 35℃
Battery Protection	Over Charge	4.275 ± 50mV
	Over Discharge	2.5 ± 50mV
	Over Current	3A - 5A
	Short Circuit	Yes
Mechanical Data	Dimension	67×58×4 mm
	Weight	41 g
	Battery Terminals	WC/FL*

*WC=With Connector FL=Flying Leads

Specifications are subject to change without notice.